



## MANGUERAS INDUSTRIALES



## TIMBERDUC PUR 533 AS

Material: hard wearing polyurethane PrePUR, braided copper wire  
The wall thickness: 0,8 mm  
Temperature: -40 to + 90C (briefly + 125 C)  
AS - antistatic standard 10E9 Ohm  
Smooth inside, flexible, resistant microbes, hydrolysis, UV, ozone  
Diameter range: 40 to 400 mm  
Length of storage: 10,15 m.b.



## TIMBERDUC PUR 532 AS

Material: hard wearing polyurethane PrePUR, braided copper wire  
The wall thickness: 0,6 mm  
Temperature: -40 to + 90C (briefly + 125 C)  
AS - antistatic standard 10E9 Ohm  
Light execution, flexible, compressible 3:1, resistant microbes, hydrolysis, UV, ozone  
Diameter range: 40 to 400 mm  
Length of storage: 10,15 m.b.



## PROTAPE PUR 301 AS

Material: hard wearing polyurethane PrePUR, braided stainless steel wire spring, folic hose  
The wall thickness: 0,4 mm  
Temperature: -40 to + 90C (briefly + 125 C)  
AS - antistatic standard 10E9 Ohm  
Very light execution, very flexible, compressible 3:1, resistant microbes, hydrolysis, UV, ozone  
Diameter range: 38 to 500 mm



# HOSE ACCESSORIES





BARDUC

381

PVC



Material: PVC, braided stainless steel wire spring. The wall thickness of 3 to 7 mm in depends on the diameter. Temperature: -20 to + 70°C (briefly + 80°C) Heavy execution, suction and discharge hose, smooth inside and outside, very good resistance to pressure and vacuum. Diameter range: 10 to 102 mm Length of storage: 30 and 60 m.b. (10-35 mm diameters).

NORPLAST PVC 384



Material: Soft PVC wall, hard PVC braid, The wall thickness of from 4 to 6 mm depends on the diameter. Temperature: -5 to + 70°C (briefly + 80°C) Industrial hose, smooth inside. Diameter range: 32 to 100 mm Length of storage: 25 i 50 m.b. (diameter 10-35 mm)

EVA 373 standard, AS i EC



Material: PVC self-supporting profile, open geometry, very light. Temperature: - 25 to + 65°C extraction hose, crush resistant - for industrial vacuum cleaners and home. Diameter range: 25, 32, 38, 40, 50 mm Length of storage: 30 m.b. Options occurrence: Standard (gray), AS (black anti-static), EC (black electrically conductive).

### NORPLAST PUR-PVC 385AS



Material: Polyurethane wall, hard PVC braid, The wall thickness of from 4 to 6mm diameter depends on the Temperature: -20 to + 70C (briefly + 80C) Industrial hose, inside smooth, very flexible, hard wearing, anti-static AS-10Eg ohms. Diameter range: 20 to 200 mm Length of storage: 10 and 20 m.b.

### HEAT-RESISTANT HOSES



Material and construction: steel strip galvanized clamped on a properly impregnated fabric. Also, multi-layered fabric. Protection against abrasion by external profile. Temperature: -40 to 1100C depending on the material. Temperatures: 170C, 260C, 300C, 400, 600, 900C. Diameter range 38 to 1200 mm depending on the heat resistance. Lengths: Any of 1 m.b.

### HOSES NEO/SIL ONE-LAYER AND DOUBLE LAYER



Suction and blast hose to hot and cold air, smooth inside, very flexible, airtight, very light. Length: 4mb SIL - temp. -70 To + 260C (short-term + 300C) glass cloth coated with silicone. NEO - temp. -35 To + 135C (short-term + 150C) glass fabric coated with neoprene.

## AIRDUC PUR 355 AS



Material: hard wearing polyurethane  
PrePUR, braided copper wire  
The wall thickness: 1,5mm  
Temperature: -40 to + 90C (briefly + 125 C)  
AS - antistatic standard 10E9 Ohm, heavy  
execution, extremely resistant to  
abrasion,  
OV, ozone.  
Diameter range: 40 to 500 mm  
Length of storage: 10,15 m.b.

## METAL HOSES

Material and construction: metal strip, sealing glass fiber Temperatures: to 120 C, to 400 C, to 600 C (INOX) Diameter range: 20 to 500 mm Flexible hose, durable, flame resistant, very good heat resistance Meet the requirements of ATEX. Length: 5,10 m.b Possible other sections in whole meters.





**ARCMEX**

ROBOTICS S.A. de C.V.

[www.arcmex.com](http://www.arcmex.com)

*Pasión por la Robótica*

México

[ventas@arcmex.com](mailto:ventas@arcmex.com)

(+52) 311-197-7225

(+52) 311-743-1674

(+32) 311-392-6634

Colombia

[ventas@arcmex.com](mailto:ventas@arcmex.com)

(+57) 304-455-9350

(+57) 300-983-8861

(+57) 322-873-5720

(+57) 324-612-1176